


<b>Max load:</b>	- lb	- kg
<b>Volume:</b>	.54 cord of 8 ft	1.95 m <sup>3</sup>
<b>Area tip to tip:</b>	8.61 ft <sup>2</sup>	.80 m <sup>2</sup>
<b>Rotator lifting capacity:</b>	- lb	- kg
<b>Torque at relief pressure:</b>	23260 lb-in	2628 Nm
	1450 psi	100 bars
<b>Weight:</b>	3045 lb	1381 kg

<b>Rotator</b>	<b>Maximum pressure:</b> 5000 psi    345 bars	<b>Recommended flow:</b> 9 gpm    34 l/min
Rotator recommended flow will produce a maximum speed of 25 rpm		

Cylinder	Diameter	Recommended pressure	Pressure range	Flow range	Lock valves
Standard	3 " (76 mm)	4300 psi (296 bars)	3600 - 5000 psi (248-345 bars)	19 - 26 gpm (72-98 l/min.)	No

Grapple cylinder maximum flow will theoretically produce a complete grapple open/close cycle in 5 seconds.



Options:

- 
- 
- 
- 

web site: [www.rotobec.com](http://www.rotobec.com)

email: [rotobec@rotobec.com](mailto:rotobec@rotobec.com)

**Rotobec Inc.:** Head office serving OEM's and Eastern Canada    Ph: (418) 383-3002 Fax: (418) 383-5334  
**Rotobec West:** Branch serving Western Canada and Western USA    Ph: (250) 765-1161 Fax: (250) 765-0035  
**Rotobec USA:** Branch serving Eastern and Central USA    Ph: (603) 444-2103 Fax: (603) 444-0327

We reserve the right to change specifications and to improve our products without notice or obligation.

07005-2244  
01/02/2022 D.L.